

# The smart downlight, done right.

One recessed fixture. Every shade of white — from a candle-warm 2200 K to crisp 6000 K daylight — dimmable to a flicker-free glow and controlled straight from your phone. No hub, no gateway. Just Wi-Fi, Powered by Shelly. ETL listed for 110-277 V North American installations.



**600** lm  
OUTPUT

**95** CRI  
COLOR

**8** W  
POWER

**2200–6000** K  
TUNABLE WHITE

**5** yr  
WARRANTY

## No hub. No gateway. Just Wi-Fi.

Every fixture ships with an integrated Smart LED Driver Powered by Shelly. Pair it to Wi-Fi in seconds, group rooms, schedule scenes, and control it with the app, Amazon Alexa or Google Home — no proprietary bridge to buy or maintain.

Two sizes.

One smart platform.

COMPACT



HiluX DS8 US

The compact recessed spot — for tighter ceiling layouts and detail lighting.

Ø 3.5"

FACE Ø90 MM

2.7-3.3"

CUT-OUT Ø68-83 MM

1.6"

DEPTH 41 MM

4-INCH



HiluX DS4 US

The 4-inch fixture built to the US recessed-can standard. Same LED, same driver.

Ø 4-5/7"

FACE Ø120 MM

4-1/5"

CUT-OUT Ø106 MM

2-2/7"

DEPTH 58 MM

SHARED

SPECIFICATIONS

|                 |                                             |
|-----------------|---------------------------------------------|
| LUMINOUS FLUX   | 600 lm                                      |
| POWER           | 8 W · PF 0.9                                |
| COLOR RENDERING | CRI 95 (Ra95)                               |
| COLOR TEMP.     | 2200-6000 K tunable + warm dim              |
| DIMMING         | App + in-app schedules, 1-100%              |
| INPUT VOLTAGE   | 110-277 VAC · 50/60 Hz                      |
| DRIVER OUTPUT   | 30-38 VDC · 170 mA                          |
| CONTROL         | Wi-Fi · Powered by Shelly                   |
| WORKS WITH      | Shelly app · Alexa · Google Home            |
| BEAM / TILT     | Adjustable gimbal, tiltable head            |
| CERTIFICATION   | ETL Listed — UL 1598 / CSA C22.2 No.250.0   |
| WARRANTY        | 5-year limited                              |
| IN THE BOX      | Fixture · smart driver · steel junction box |



Daisy-chain ready.

Push-in lever connectors loop line, neutral & ground from fixture to fixture — one whip, whole rooms wired fast. Junction box included.

WHY INSTALLERS PICK HILUX

- No bridge to sell or support — native Wi-Fi
- High color rendering — CRI 95 (Ra95), true whites
- Lever-nut connectors — tool-free, fast daisy-chaining spot to spot
- ETL listed for US & Canada, 110-277 V
- Included junction box with knockouts
- Flicker-free dimming to 1%